

**PROJECT :**
**DATE :**
**AREA :**
**TYPE :**

## PRODUCT SPECIFICATION

|                                 |                                       |
|---------------------------------|---------------------------------------|
| <b>Model No.</b>                | : IR30797-25W                         |
| <b>Materials</b>                | : Aluminium housing                   |
|                                 | : Finished in polyester powder coated |
| <b>Lamp</b>                     | : COB LED 25W                         |
| <b>Socket</b>                   | : -                                   |
| <b>Color Temperature</b>        | : 2700K/3000K/4000K/6500K             |
| <b>Beam Angle</b>               | : 8°/15°/24°/38°/65°                  |
| <b>Luminous Flux</b>            | : 2250lm                              |
| <b>CRI</b>                      | : Ra≥90                               |
| <b>Working Temperature</b>      | : -20°C - +40°C                       |
| <b>Transformer Availability</b> | : Included                            |
| <b>Transformer Mounting</b>     | : Remote                              |
| <b>Aiming</b>                   | : Directional                         |
| <b>Optic Direction</b>          | : Adjustable 0° - 30°, Rotation 350°  |
| <b>Light Distribution</b>       | : Symmetric                           |
| <b>Lamp Lifetime</b>            | : 40000 Hrs                           |
| <b>Dimension</b>                | : L: 105 x W: 105 x H: 146 mm         |
| <b>Cut-Out</b>                  | : L: 95 x W:95 mm                     |
| <b>Cut-Out shape</b>            | : Square                              |
| <b>Mounting</b>                 | : Recessed                            |
| <b>Finishing Color</b>          | : White/Black                         |
| <b>Cut-Off Angle</b>            | : -                                   |
| <b>Unified Glare Rating</b>     | : UGR<19                              |
| <b>Control Method</b>           | : 36V 600mA                           |
| <b>Dimmable System</b>          | : Non-dim/0-10V/Triac/DALI            |
| <b>IP Rating</b>                | : IP65                                |
| <b>Accessories</b>              | : -                                   |
| <b>Remarks</b>                  | :                                     |

