

**PROJECT :****DATE :****AREA :****TYPE :****PRODUCT SPECIFICATION**

<b>Model No.</b>	: IC30141
<b>Materials</b>	: Aluminium housing
	: Finished in polyester powder coated
<b>Lamp</b>	: QR-CBC51 Max 50W
<b>Socket</b>	: GU5.3
<b>Color Temperature</b>	: As per require
<b>Beam Angle</b>	: As per require
<b>Luminous Flux</b>	: As per require
<b>CRI</b>	: As per require
<b>Working Temperature</b>	: -20°C - +40°C
<b>Transformer Availability</b>	: Remote
<b>Transformer Mounting</b>	: Remote
<b>Aiming</b>	: Directional
<b>Optic direction</b>	: Adjustable 0° - 30°
<b>Light Distribution</b>	: Symmetric
<b>Lamp lifetime</b>	: As per require
<b>Dimension</b>	: W: 185 x L: 185 x H: 140 mm
<b>Cut-Out</b>	: W: 172 x L: 172 mm
<b>Cut-Out shape</b>	: Square
<b>Mounting</b>	: Recessed
<b>Finishing Color</b>	: As per require
<b>Cut-Off Angle</b>	: -
<b>Control Method</b>	: 12V
<b>Dimmable System</b>	: As per require
<b>IP Rating</b>	: IP20
<b>Accessories</b>	: -
<b>Remarks</b>	: -

